

Product sheet **BEESAFE**



PRIX DE
L'INNOVATION
Préventica
SANTÉ/SÉCURITÉ AU TRAVAIL
LYON EUREXPO 2018

#ECHELLE CANADA

ECHELLE CANADA EXCLUSIVITY

CONFORMS WITH STANDARDS **NF P93-520 / NF EN ISO 14122-2/3/4**

DESCRIPTION

ECHELLE CANADA has developed and patented a new technology for assisting the lifting of platforms by hydraulic assistance.

The BEESAFE concept is unique, allowing precise working heights on fixed or mobile platforms.

The product is manufactured according to the user's requirements, which implies a multitude of possible combinations within the limits of the standards to which we refer.

BEESAFE products provide unequalled **comfort, ease and speed of lifting**.

BENEFITS

Customised design.

Maintenance reduced to a minimum without external intervention (VGP).

BEESAFE products are not PEMP, so there is no need to obtain the CACES R 386.

The adjustment of the platform is millimetric from the ground.

OPTIONS

Front and / or lateral offset.

Protective cover for the chassis.

Dismantled or semi-dismantled guardrails for doors passage.

Saloon type gate of portillon.



Maintenance in the transport sector



Daily use



Maintenance in an industrial environment

Product sheet **BEESAFE**



**PRIX DE
L'INNOVATION
Préventica**
SANTÉ/SÉCURITÉ AU TRAVAIL
LYON EUREXPO 2018

#ECHELLE CANADA

ECHELLE CANADA EXCLUSIVITY

CONFORMS WITH STANDARDS **NF P93-520 / NF EN ISO 14122-2/3/4**

TECHNICAL CHARACTERISTICS

GENERAL INFORMATIONS

- The dimensions of the platform can be fully customised
- Bespoke platform length : 39" - 79"
- Bespoke platform width : 20" - 47"
- Bespoke frontal deflection length : 28" max in fixed version, 20" max in removable version
- Bespoke side deflection length : 12" max
- Variable platform height :
 - Ⓐ Stroke (simple chisel) : 22"
 - Ⓑ Stroke (double chisel) : 43"
- Table height adjusted following the request and the choice between Ⓐ and Ⓑ : 91" max
- Type of access on platform: vertical ladder
- Securing of the access : gate or door saloons
- Capacity : 551 lb - 2 persons
(Excluding the case of the front offset : 331 lb - 1 person)
- Approved for 1 to 2 users following the configuration

PLATFORM SECURISATION

Platform securisation
with strap or security gate



PLATFORM LOCKING
at the height requested



**TECHNOLOGIE
BEESAFE**
HYDRAU-ACCESS

**ELEVATION
HYDRAULIC LIFTING**
of the platform by simple press



REDESCENT
of the platform facilitated
by a handle



EQUIPPED WITH 4
wheels with brakes



FEET
with millimetre adjustment for
telescopic stabilizers (optional)